

**IN THE CLAIMS:**

Please amend claims 1, 5, 12, 15, 19, and 20 as follows. Please cancel claim 18 without prejudice or disclaimer.

1. (Currently Amended) A system, comprising:

a mobile node belonging to a home network located within a secure network, the mobile node having a network interface configured to communicate with other nodes, the mobile node having only one security association and only one mobility binding with a home agent so as to provide secure mobile connectivity that implements a mobile internet protocol home agent functionality;

a proxy home agent connected to the home network and located within the secure network, wherein the proxy home agent is configured to provide a proxying functionality;

the home agent located outside of the secure network, wherein the home agent is configured to provide a signaling and tunneling functionality and to notify the proxy home agent of the mobile node; and

a virtual private network gateway located outside the secure network and configured to work in conjunction with the home agent;

a demilitarized zone located outside the secure network, wherein the virtual private network gateway and the home agent reside in the demilitarized zone;

a first firewall between the secure network and the demilitarized zone; and

a second firewall between the demilitarized zone and an external network configured to deny communications from the external network with a source address in the known range.

2. (Previously Presented) The system of claim 1, wherein the virtual private network gateway and the home agent are located within a single device within a demilitarized zone.

3. (Previously Presented) The system of claim 1, further comprising a firewall coupled to the secure network and the virtual private network gateway, wherein the home agent is located within the firewall.

4. (Previously Presented) The system of claim 1, wherein the home agent is a separate device from the virtual private network gateway.

5. (Currently Amended) The system according to claim 1, ~~further comprising:~~  
~~a demilitarized zone located outside the secure network, wherein the virtual private network gateway and the home agent reside in the demilitarized zone; a first firewall between the secure network and the demilitarized zone; and~~

~~a second firewall between the demilitarized zone and an external network configured to deny communications from the external network with a source address in the known range,~~

wherein the mobile node has a permanent address in a known range.

6. (Previously Presented) The system according to claim 1, further comprising:

a demilitarized zone located outside the secure network,

wherein the virtual private network gateway and the home agent reside in the demilitarized zone; and

a first firewall between the secure network and the demilitarized zone,

wherein the mobile node has a permanent address in a known range and the first firewall is programmed to deny all communications from the demilitarized zone with a source address in the known range, and

wherein the virtual private network gateway has a direct connection to an internal interface of the first firewall such that the first firewall considers the virtual private network gateway transmitted data as internal to the secure network.

7. (Previously Presented) The system of claim 1, further comprising:

a demilitarized zone comprising a first router coupled to a second router that is coupled to a firewall, the virtual protocol network gateway coupled to the first router, and

the firewall, wherein the home agent is coupled to the first router.

8. (Previously Presented) The system of claim 7, wherein packets from the mobile node destined toward nodes inside the secure network first go the home agent and then to the virtual protocol network gateway that is configured to forward the packets through the firewall to the secure network.

9. (Previously Presented) The system of claim 8, wherein packets from the second router to the firewall having a source address in a known range are dropped by the firewall.

10. (Previously Presented) The system according to claim 1, wherein a router is directly connected to a firewall, and the virtual protocol network gateway and the home agent are configured to connect to a different interface of the router and the firewall.

11. (Previously Presented) The system of claim 10, wherein the firewall is configured such that it considers the interface with which it connects to the virtual protocol network gateway as an internal interface and packets with a source address that are outside of a known address range received on the internal interface are dropped, and packets with a source address that are within the known address range that are received by the firewall on an external interface are dropped.

12. (Currently Amended) The system of claim 11, wherein virtual protocol network encapsulated packets are forwarded to the virtual protocol network gateway and when a security association exists, the packet is decrypted and forwarded to the firewall on the internal interface and when a security association does not exist the packet is dropped.

13. (Previously Presented) The system of claim 12, wherein mobile internet protocol packets and virtual protocol network encapsulated packets first reach the home agent which are forwarded to the virtual protocol network gateway and then to the secure network through the firewall's internal interface.

14. (Previously Presented) The system of claim 1, further comprising:  
a firewall coupled to the secure network and the virtual protocol network gateway;  
and  
a router comprising an access control list used to drop packets that have a source address that belong to a known address range.

15. (Currently Amended) A method, comprising:

establishing a proxy home agent located within the secure network to monitor data directed to the mobile node so as to secure communication between a mobile node associated with a home network in a secure network and a correspondent node;

establishing a home agent configured to create only one security association with the mobile node and only one mobility binding with the mobile node and to notify the proxy home agent of the mobile node;

collecting data directed to the mobile node;

packaging the collected data in a virtual private network secure tunnel to an internal address of the mobile node to create virtual protocol network packaged data; and

tunneling the virtual protocol network packaged data to a current address of the mobile node; and

packaging the collected data in an internet-protocol-in-internet-protocol tunnel and sending it to a virtual protocol network device for virtual protocol network encryption and tunneling the virtual protocol network packaged data to the current address of the mobile node.

16. (Previously Presented) The method of claim 15, wherein the virtual protocol network secure tunnel follows the internet protocol security protocol.

17. (Previously Presented) The method of claim 15, wherein the tunneling of the virtual protocol network packaged data to the external mobile node occurs according to the internet protocol mobility protocol.

18. (Canceled)

19. (Currently Amended) A system, comprising:

means for establishing a proxy home agent located within a secure network to monitor data directed to a mobile node so as to secure mobile connectivity that implements mobile internet protocol home agent functionality via distributed components;

means for establishing a home agent configured to create only one security association with the mobile node and only one mobility binding with the mobile node and to notify the proxy home agent of the mobile node;

means for collecting data directed to the mobile node;

means for packaging the collected data in a virtual private network secure tunnel to an internal address of the mobile node to create virtual private network packaged data;

means for tunneling the virtual private network packaged data to a current address of the mobile node;

means for the home agent to communicate to the proxy home agent that the mobile node has moved outside its home network;

means for the home agent to communicate to the proxy home agent that the mobile node has come back to its home network; and

means for enabling the proxy home agent to create and remove a proxy address resolution protocol entry for a permanent address associated with the mobile node;

means for providing a demilitarized zone located outside the secure network, wherein the virtual private network gateway and the home agent reside in the demilitarized zone, and a firewall between the secure network and the demilitarized zone;  
and

means for providing a second firewall between the demilitarized zone and providing an external network configured to deny communications from the external network with a source address in the known range

20. (Currently Amended) A computer program embodied on a computer readable medium, the computer program being configured to control a processor to perform:

establishing a proxy home agent located within a secure network to monitor data directed to a mobile node;

establishing a home agent configured to create only one security association with the mobile node and only one mobility binding with the mobile node and to notify the proxy home agent of the mobile node;

collecting data directed to the mobile node;

packaging the collected data in a virtual private network secure tunnel to an internal address of the mobile node to create virtual private network packaged data; ~~and~~

tunneling the virtual private network packaged data to a current address of the mobile node; and

packaging the collected data in an internet-protocol-in-internet-protocol tunnel and sending it to a virtual protocol network device for virtual protocol network encryption and tunneling the virtual protocol network packaged data to the current address of the mobile node.

21. (New) The system according to claim 19, wherein the mobile node has a permanent address in a known range.